ESSENTIAL CHEMICAL

EC 356

Defoamer

Application

EC-356 Defoamer is a water dispersible silicone emulsion formulated for use as a foam control agent in carpet cleaning equipment. This product will prevent and destroy unwanted foam wherever it needs to be controlled

Product Utilization

- Cooling towers, chillers, Evaporator condensers foam control
- Food Processing industries
- Pulp & Paper industries
- General defoaming requirements
- Water treatment industries

Dosage Requirements

Every process system or discharge is different. Anti-foam concentrations should be tailored to actual use conditions. Adjust the concentration to the point where the foam level can be realistically tolerated. The amount to do this will depend on the degree of foam suppression required, the foam components, and other factors. Start with a capful and note the results. Add as need to achieve best results using the least amount of product possible. Using too much can cause the opposite effect.

For Carpet Cleaning Equipment

Use approximately ¼ oz. to 1 oz. depending on the size of the holding tank. NEVER add to the solution that is being used for the cleaning. Add ONLY to the recovery tank.

Product Data

- Product #: EC-356
- Color: Opaque
- Density: 8.4 lb./gal.
- Viscosity: Medium
- pH: 7.0 – 7.5
- Stability: May be used in acid or alkali solutions.
- Flash Point: none
- Odor: None appreciable
- DOT: Non-Regulated

Limitations and Handling

- Keep it away from children.
- Do not pour into improperly labeled containers.
- Safety Data Sheets are available in compliance with the worker's "Right To Know Law"